



SPECI

SPECI


SPECCHI _ Mirrors _ Miroirs _ Spiegel



.09



.23



.32





EUROPA

58100-58104-58108-58112-58116-58120-58124-58128-58132

Specchio con telaio in alluminio verniciato. Con luce frontale.

Mirror with painted aluminium frame. Front light. / Miroir avec cadre couleur aluminium satiné. Lumière supérieure.
Spiegel mit lackiertem Aluminiumrahmen. Oberes unteres Umgebungslicht.



Temperatura del colore della luce
Color temperature
Température de couleur
Lichtfarbtemperatur

cod.	EAN	H mm	L mm	Sp mm.	Lumen/mt	Watt	KG	
58100	8056188432630	800	600	45	1700	12	8	1
58104	8056188432579	800	700	45	1700	13	10	1
58108	8056188432517	800	800	45	1700	14	12	1
58112	8056188432456	800	900	45	1700	15	13	1
58116	8056188432395	800	1000	45	1700	16	14	1
58120	8056188432333	800	1100	45	1700	17	15	1
58124	8056188432272	800	1200	45	1700	18	16	1
58128	8056188432210	800	1300	45	1700	19	17	1
58132	8056188432159	800	1400	45	1700	20	18	1

Peso e volume lordo / Gross weight and volume / Poids et volume brut / Bruttogewicht und Volumen

PULIZIA e MANUTENZIONE

Pulire con un sapone neutro, applicare con un panno umido, strofinare leggermente, lasciar agire brevemente e quindi sciacquare con acqua. Infine lucidare con un panno morbido e asciutto. Per macchie di calcare pulire con una soluzione di acqua (80%) e aceto bianco (20%), per un'azione igienizzante aggiungere alla soluzione del bicarbonato di sodio. Asciugare sempre la superficie in modo da evitare le macchie derivanti dall'acqua.

Avvertenze: La resistenza alla corrosione al nichel-cromo si riduce sotto l'azione di acidi e composti alogenati (cloruri, bromuri, ioduri). Non utilizzare mai soluzioni a base di cloro (candeggina), detersivi o spugne abrasive. Evitare la ruggine causata da materiali esterni (ad es. paglietta di acciaio ecc.).

CARE and MAINTENANCE



Clean with a mild soap, apply with a damp cloth, rub lightly, leave it briefly and then rinse with water. Finally polish with a soft, dry cloth. To remove the limestone stains, clean with a solution of water (80%) and white vinegar (20%), to sanitize add baking soda. Always dry the surface in order to prevent stains caused by water. Warnings: The corrosion resistance of the steel is reduced by acids and halogen compounds (chlorides, bromides, iodides). Never use solutions containing chlorine (bleach), detergents or abrasive sponges. Prevent rust caused by external materials (eg. Scouring steel, etc..).

EUROPA



58102-58106-58110-58114-58118-58122-58126-58130-58134

Specchio con telaio in alluminio verniciato. Luce frontale e ambientale superiore/inferiore.

Mirror with painted aluminium frame. Front and upper / lower ambient light. / Miroir avec cadre couleur aluminium satiné. Lumière supérieure et d'ambiance supérieure / inférieure. / Spiegel mit lackiertem Aluminiumrahmen. Umgebungslicht vorne und oben / unten.



Temperatura del colore della luce
Color temperature
Température de couleur
Lichtfarbtemperatur

cod.	EAN	H mm	L mm	Sp mm.	Lumen/mt	Watt		
58102	8056188432609	800	600	45	900	25	8	1
58106	8056188432548	800	700	45	900	28	9	1
58110	8056188432487	800	800	45	900	31	10	1
58114	8056188432425	800	900	45	900	35	11	1
58118	8056188432364	800	1000	45	900	38	12	1
58122	8056188432302	800	1100	45	900	41	13	1
58126	8056188432241	800	1200	45	900	44	14	1
58130	8056188432180	800	1300	45	900	48	15	1
58134	8056188432128	800	1400	45	900	51	16	1

Peso e volume lordo / Gross weight and volume / Poids et volume brut / Bruttogewicht und Volumen

PULIZIA e MANUTENZIONE

Pulire con un sapone neutro, applicare con un panno umido, strofinare leggermente, lasciar agire brevemente e quindi sciacquare con acqua. Infine lucidare con un panno morbido e asciutto. Per macchie di calcare pulire con una soluzione di acqua (80%) e aceto bianco (20%), per un'azione igienizzante aggiungere alla soluzione del bicarbonato di sodio. Asciugare sempre la superficie in modo da evitare le macchie derivanti dall'acqua.

Avvertenze: La resistenza alla corrosione al nichel-cromo si riduce sotto l'azione di acidi e composti alogenati (cloruri, bromuri, ioduri). Non utilizzare mai soluzioni a base di cloro (candeggina), detersivi o spugne abrasive. Evitare la ruggine causata da materiali esterni (ad es. paglietta di acciaio ecc.).

CARE and MAINTENANCE


Clean with a mild soap, apply with a damp cloth, rub lightly, leave it briefly and then rinse with water. Finally polish with a soft, dry cloth. To remove the limestone stains, clean with a solution of water (80%) and white vinegar (20%), to sanitize add baking soda. Always dry the surface in order to prevent stains caused by water. Warnings: The corrosion resistance of the steel is reduced by acids and halogen compounds (chlorides, bromides, iodides). Never use solutions containing chlorine (bleach), detergents or abrasive sponges. Prevent rust caused by external materials (eg. Scouring steel, etc..).

EUROPA

58103-58107-58111-58115-58119-58123-58127-58131-58135

Specchio con telaio in alluminio verniciato. Luce frontale e ambientale superiore/inferiore.

Mirror with painted aluminium frame. Front and upper / lower ambient light. / Miroir avec cadre couleur aluminium satiné. Lumière supérieure et d'ambiance supérieure / inférieure. / Spiegel mit lackiertem Aluminiumrahmen. Umgebungslicht vorne und oben / unten.



Temperatura del colore della luce
Color temperature
Température de couleur
Lichtfarbtemperatur

cod.	EAN	H mm	L mm	Sp mm.	Lumen/mt	Watt	kg	
58103	8021586758941	800	600	45	900	63	8	1
58107	8021586758910	800	700	45	900	66	9	1
58111	8021586758880	800	800	45	900	69	10	1
58115	8021586758859	800	900	45	900	100	11	1
58119	8021586758828	800	1000	45	900	103	12	1
58123	8021586758798	800	1100	45	900	146	13	1
58127	8021586758767	800	1200	45	900	149	14	1
58131	8021586758736	800	1300	45	900	153	15	1
58135	8021586758705	800	1400	45	900	156	16	1

Peso e volume lordo / Gross weight and volume / Poids et volume brut / Bruttogewicht und Volumen

PULIZIA e MANUTENZIONE

Pulire con un sapone neutro, applicare con un panno umido, strofinare leggermente, lasciar agire brevemente e quindi sciacquare con acqua. Infine lucidare con un panno morbido e asciutto. Per macchie di calcare pulire con una soluzione di acqua (80%) e aceto bianco (20%), per un'azione igienizzante aggiungere alla soluzione del bicarbonato di sodio. Asciugare sempre la superficie in modo da evitare le macchie derivanti dall'acqua.

Avvertenze: La resistenza alla corrosione al nichel-cromo si riduce sotto l'azione di acidi e composti alogenati (cloruri, bromuri, ioduri). Non utilizzare mai soluzioni a base di cloro (candeggina), detersivi o spugne abrasive. Evitare la ruggine causata da materiali esterni (ad es. paglietta di acciaio ecc.).

CARE and MAINTENANCE

Clean with a mild soap, apply with a damp cloth, rub lightly, leave it briefly and then rinse with water. Finally polish with a soft, dry cloth. To remove the limestone stains, clean with a solution of water (80%) and white vinegar (20%), to sanitize add baking soda. Always dry the surface in order to prevent stains caused by water. Warnings: The corrosion resistance of the steel is reduced by acids and halogen compounds (chlorides, bromides, iodides). Never use solutions containing chlorine (bleach), detergents or abrasive sponges. Prevent rust caused by external materials (eg. Scouring steel, etc.).

PLUS DI PRODOTTO

Product advantage
 Avantage du produit
 Avantage du produit



Made in Italy
 Made in Italy
 Made in Italy
 Made in Italy



Installazione non reversibile
 Not reversible installation
 Installation non réversible
 NICHT reversible installation



Marcatura CE
 CE mark
 Label CE
 CE Kennzeichen



Articolo con led
 Article with leds
 Article avec led
 Artikel mit LED



IP44
 IP44
 IP44
 IP44



LED sostituibili
 Replaceable leds
 LED remplaçables
 Austauschbare LEDs



Regolazione dell'intensità della luce
 Light intensity adjustment
 Réglage de l'intensité lumineuse
 Lichtintensitätsregelung



Accensione con tastiera
 Activation by keyboard
 Panneau de controle tactile
 Anschalten durch eine Tastatur



Accensione da interruttore
 Switch on
 Allumer
 Einschalten